

Part of Thermo Fisher Scientific

SAFETY DATA SHEET

Creation Date 13-Feb-2012

Revision Date 26-Jan-2015

Revision Number 1

	1. Identification
Product Name	Cytoseal™ 60
Cat No. :	23244256
Synonyms	No information available
Recommended Use	Laboratory chemicals.
Uses advised against Details of the supplier of the safety	No Information available v data sheet
Company Richard Allan Scientific A Subsidiary of Thermo Fisher Scient 4481 Campus Drive Kalamazoo, MI 49008	Emergency Telephone Number Chemtrec US: (800) 424-9300 ific Chemtrec EU: 001 (202) 483-7616

2. Hazard(s) identification

Classification

Г

Tel: (800) 522-7270

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Skin Corrosion/irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Reproductive Toxicity	Category 1B
Specific target organ toxicity (single exposure) Target Organs - Central nervous system (CNS).	Category 3
Specific target organ toxicity - (repeated exposure) Target Organs - Kidney, Liver, Heart, Blood.	Category 1
Aspiration Toxicity	Category 1

Label Elements

Signal Word Danger

Hazard Statements

Highly flammable liquid and vapor May be fatal if swallowed and enters airways Causes skin irritation Causes serious eye irritation May cause drowsiness or dizziness May damage fertility or the unborn child Causes damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

IF exposed or concerned: Get medical attention/advice

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Toxic to aquatic life with long lasting effects

Unknown Acute Toxicity

.? % of the mixture consists of ingredients of unknown toxicity.

3. Composition / information on ingredients

Component	CAS-No	Weight %
Acrylic Resin	28262-63-7	25 - 28
Butyl benzyl phthalate	85-68-7	4 - 6
2,6-Di-tert-butyl-p-cresol	128-37-0	< 1.0

Toluene		108-88-3	65 - 68		
4. First-aid measures					
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.				
Skin Contact	Wash off imr	nediately with plenty of water for at leas	t 15 minutes. Obtain medical attention.		
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a respiratory medical device. Immediate medical attention is required.				
Ingestion	Do not induce vomiting. Call a physician or Poison Control Center immediately.				
Most important symptoms/effects	Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like				
Notes to Physician	headache, dizziness, tiredness, nausea and vomiting Treat symptomatically				
		re-fighting measures			
Suitable Extinguishing Media	CO 2, dry che containers.	emical, dry sand, alcohol-resistant foam.	Use water spray to cool unopened		
Unsuitable Extinguishing Media	Water may b	e ineffective			
Flash Point	4.44 °C / 4	10 °F			
Method -	No information	on available			
Autoignition Temperature Explosion Limits	No information	on available			
Upper	No data avai				
Lower	No data avai				
Sensitivity to Mechanical Impact Sensitivity to Static Discharge	No information No information				
Specific Hazards Arising from the Chemical Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.					
Hererdeus Combustion Products					

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO₂)

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA Health 3	Flammability 3	Instability 0	Physical hazards N/A
	6. Accidental rel	ease measures	
Personal Precautions		uipment. Remove all sources of charges. Do not get in eyes, o	of ignition. Take precautionary n skin, or on clothing.
Environmental Precautions		the environment. See Section o the environment. Collect spi	0
Methods for Containment and Cl Up		on. Soak up with inert absorb charges. Keep in suitable, clos	

7. Handling and storage

Handling

Use only under a chemical fume hood. Wear personal protective equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Flammables area.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
2,6-Di-tert-butyl-p-cresol	TWA: 2 mg/m ³	(Vacated) TWA: 10 mg/m ³	TWA: 10 mg/m ³
Toluene	TWA: 20 ppm	(Vacated) TWA: 100 ppm	IDLH: 500 ppm
		(Vacated) TWA: 375 mg/m ³	TWA: 100 ppm
		Ceiling: 300 ppm	TWA: 375 mg/m ³
		(Vacated) STEL: 150 ppm	STEL: 150 ppm
		(Vacated) STEL: 560 mg/m ³	STEL: 560 mg/m ³
		TWA: 200 ppm	

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
2,6-Di-tert-butyl-p-cresol	STEL: 10 mg/m ³	TWA: 10 mg/m ³ STEL: 20 mg/m ³	TWA: 2 mg/m ³
Toluene	TWA: 50 ppm TWA: 188 mg/m³ Skin	TWA: 50 ppm TWA: 188 mg/m³	TWA: 20 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures	Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.
Personal Protective Equipment	
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

	9. Physical and chemical properties
Physical State	Liquid
Appearance	Colorless
Odor	aromatic
Odor Threshold	No information available
рН	No information available
Melting Point/Range	No data available
Boiling Point/Range	110.6 °C / 231 °F
Odor Odor Threshold pH Melting Point/Range	aromatic No information available No information available No data available

Flash Point Evaporation Rate Flammability (solid,gas) Flammability or explosive limits Upper Lower Vapor Pressure Vapor Density Relative Density Solubility Partition coefficient; n-octanol/water Autoignition Temperature Decomposition Temperature Viscosity 4.44 °C / 40 °F No information available No information available

No data available No data available 47 mmHg @ 20 °C No information available 0.97 Insoluble in water No data available No information available No information available No information available

10. Stability and reactivity

Reactive Hazard	None known, based on information available		
Stability	Stable under normal conditions.		
Conditions to Avoid	Incompatible products. Heat, flames and sparks.		
Incompatible Materials	Strong oxidizing agents, Strong acids		
Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)			
Hazardous Polymerization	Hazardous polymerization does not occur.		
Hazardous Reactions	None under normal processing.		

11. Toxicological information

Acute Toxicity

Product Information Oral LD50 Dermal LD50	Based on ATE data, the cla	n is available for this product ssification criteria are not met. A ssification criteria are not met. A		
Vapor LC50 Component Information	Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.			
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Butyl benzyl phthalate	2330 mg/kg (Rat)	6700 mg/kg (Rat)	6.7 mg/L (Rat)4 h	
2,6-Di-tert-butyl-p-cresol	890 mg/kg (Rat) >2000 mg/kg(Rat)	2000 mg/kg (Rat)	Not listed	
Toluene	> 5000 mg/kg (Rat)	12000 mg/kg (Rabbit)	26700 ppm (Rat)1 h	
Toxicologically Synergistic Products	No information available			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes and skin

Sensitization No information available

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Acrylic Resin	28262-63-7	Not listed				
Butyl benzyl phthalate	85-68-7	group 3	Not listed	Not listed	Not listed	Not listed
2,6-Di-tert-butyl-p-cres ol	128-37-0	Not listed				
Toluene	108-88-3	Not listed				

Mutagenic Effects	Mutagenic effects have occurred in humans.				
Reproductive Effects	Experiments have shown reproductive toxicity effects on laboratory animals.				
Developmental Effects	Developmental effects have occurred in experimental animals.				
Teratogenicity	Teratogenic effects have occurred in experimental animals.				
STOT - single exposure STOT - repeated exposure	Central nervous system (CNS) Kidney Liver Heart Blood				
Aspiration hazard	No information available				
• • • • • • • • •					

delayed **Endocrine Disruptor Information**

Symptoms / effects, both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Component	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information		
Butyl benzyl phthalate	Group I Chemical	High Exposure Concern	Not applicable		
Other Adverse Effects See actual entry in RTECS for complete information.					

ctual entry in RIECS for complete information.

12. Ecological information

Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Butyl benzyl phthalate	0.02 - 0.25 mg/L EC50 96 h	Lepomis macrochirus:	Not listed	0.97 mg/L EC50 = 48 h 0.76
	0.2 - 28.2 mg/L EC50 72 h	LC50=1.7 mg/L 96h		mg/L EC50 > 48 h 0.9 - 1.1
	_	Salmo gairdneri: LC50=1.1		mg/L EC50 48 h 1.28 mg/L
		mg/L 96h		EC50 = 48 h
2,6-Di-tert-butyl-p-cresol	EC50 = 0.758 mg/L 96h	LC50 = 0.199 mg/L 96h	EC50 = 7.82 mg/L 5 min	EC50 >0.31 mg/L 48h
	EC50 = 6 mg/L 72 h		EC50 = 8.57 mg/L 15 min	
	_		EC50 = 8.98 mg/L 30 min	
Toluene	12.5 mg/L EC50 = 72 h 433	50-70 mg/L LC50 96 h	EC50 = 19.7 mg/L 30 min	11.5 mg/L EC50 = 48 h 5.46
	mg/L EC50 > 96 h	5-7 mg/L LC50 96 h	_	- 9.83 mg/L EC50 48 h
	_	15-19 mg/L LC50 96 h		_
		28 mg/L LC50 96 h		
		12 mg/L LC50 96 h		

Persistence and Degradability **Bioaccumulation/ Accumulation** No information available No information available.

Mobility

Component	log Pow
Butyl benzyl phthalate	4.91
2,6-Di-tert-butyl-p-cresol	4.17
Toluene	2.65

Waste Disposal Methods

13. Disposal considerations

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Toluene - 108-88-3	U220	-

DOT

14. Transport information

UN-No

UN1866

Proper Shipping Name Hazard Class Packing Group	RESIN SOLUTION 3 II
TDG	
UN-No	
Proper Shipping Name	RESIN SOLUTION
Hazard Class	3
Packing Group	ll
IATA	
UN-No	UN1866
Proper Shipping Name	RESIN SOLUTION
Hazard Class	3
Packing Group	II
IMDG/IMO	
UN-No	UN1866
Proper Shipping Name	RESIN SOLUTION
Hazard Class	3
Packing Group	II.
	15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Acrylic Resin	Х	Х	-	-	-		Х	Х	Х	Х	Х
Butyl benzyl phthalate	Х	Х	-	201-622-7	-		Х	Х	Х	Х	Х
2,6-Di-tert-butyl-p-cresol	Х	Х	-	204-881-4	-		Х	Х	Х	Х	Х
Toluene	Х	Х	-	203-625-9	-		Х	Х	Х	Х	Х

Legend: X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b)	Not applicable
------------	----------------

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Toluene	108-88-3	65 - 68	1.0
SARA 311/312 Hazardous Categorization Acute Health Hazard Chronic Health Hazard Fire Hazard	Yes Yes Yes		

Clean Water Act

Component	CWA - Hazardous	CWA - Reportable	CWA - Toxic Pollutants	CWA - Priority Pollutants

	Substances	Quantities		
Butyl benzyl phthalate	-	-	Х	Х
Toluene	X	1000 lb	Х	X

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Toluene	Х		-

OSHA Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Butyl benzyl phthalate	100 lb	-
Toluene	1000 lb 1 lb	-

California Proposition 65 This product contains the following Proposition 65 chemicals:

Component	CAS-No	California F	Prop. 65	Prop	65 NSRL	Category
Butyl benzyl phthalate	85-68-7	Developm	Developmental		-	Developmental
Toluene	108-88-3		Developmental - Female Reproductive		Developmental	
State Right-to-Know						
Component	Massachusetts	New Jersey	Pennsy	ylvania	Illinois	Rhode Island
Butyl benzyl phthalate	Х	Х	>	<	Х	-
2,6-Di-tert-butyl-p-cresol	Х	Х	>	<	-	Х
Toluene	Х	Х	>	<	Х	Х

U.S. Department of Transportation

Reportable Quantity (RQ):	Y
DOT Marine Pollutant	Ν
DOT Severe Marine Pollutant	Ν

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade

Serious risk, Grade 3

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class

B2 Flammable liquid D2A Very toxic materials



16. Other information

Prepared By	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com
Creation Date	13-Feb-2012
Revision Date	26-Jan-2015
Print Date	26-Jan-2015
Revision Summary	This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS)
	

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS