



D/E Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision date: 7/11/2023 Supersedes: 3/13/2018 Version: 4.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : D/E Resin

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For Rx Only

1.3. Supplier

Manufacturer

BISCO, Inc.
1100 W. Irving Park Rd.
Schaumburg, IL , 60193
U.S.A.
T 1-800-247-3368 or 1-847-534-6000
sales@bisco.com - www.bisco.com

1.4. Emergency telephone number

Emergency number : CHEMTREC - 24-Hour Hazmat Emergency Communications Center
Domestic: 1-800-424-9300 Outside the U.S.: 1-703-527-3887, collect calls accepted

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Specific target organ toxicity - Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

Precautionary statements (GHS US) : P261 - Avoid breathing fume, mist, vapors.
P264 - Wash hands thoroughly after handling
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302+P352 - If on skin: Wash with plenty of water and soap
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

D/E Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a poison center/a doctor if you feel unwell
P321 - Specific treatment (see First aid measures on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P501 - Dispose in a safe manner in accordance with local/national regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
BisGMA	CAS-No.: 1565-94-2	30 - 50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335
2-Hydroxyethyl Methacrylate	CAS-No.: 868-77-9	30 - 50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Urethane Dimethacrylate	CAS-No.: Proprietary	30 - 50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335
Triethylene Glycol Dimethacrylate	CAS-No.: 109-16-0	1 - 5	Skin Sens. 1B, H317
Ethyl 4-Dimethylaminobenzoate	CAS-No.: 10287-53-3	1 - 5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

D/E Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause respiratory irritation.
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid breathing fume, mist, vapors. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid breathing fume, mist, vapors. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

D/E Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous Liquid.
Color	: Straw
Odor	: Acrylic
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 150 °C
Flash point	: 75 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: > 1
Solubility	: No data available

D/E Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

2-Hydroxyethyl Methacrylate (868-77-9)

LD50 oral rat	5564 mg/kg body weight (Rat, Experimental value, Oral)
LD50 dermal rabbit	> 5000 mg/kg (24 h, Rabbit, Male, Experimental value, Dermal)
ATE US (oral)	5564 mg/kg body weight

Ethyl 4-Dimethylaminobenzoate (10287-53-3)

LD50 oral rat	> 2000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 15 day(s))

D/E Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethyl 4-Dimethylaminobenzoate (10287-53-3)	
ATE US (oral)	500 mg/kg body weight
Triethylene Glycol Dimethacrylate (109-16-0)	
LD50 oral rat	10837 mg/kg Source: NLM, THOMSON
LD50 dermal	> 2000 mg/kg body weight (US EPA, 14 day(s), Mouse, Male, Experimental value, Skin, 14 day(s))
ATE US (oral)	10837 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
2-Hydroxyethyl Methacrylate (868-77-9)	
pH	No data available in the literature
Triethylene Glycol Dimethacrylate (109-16-0)	
pH	6.8 - 7.2
Serious eye damage/irritation	: Causes serious eye irritation.
2-Hydroxyethyl Methacrylate (868-77-9)	
pH	No data available in the literature
Triethylene Glycol Dimethacrylate (109-16-0)	
pH	6.8 - 7.2
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
Urethane Dimethacrylate (Proprietary)	
STOT-single exposure	May cause respiratory irritation.
Ethyl 4-Dimethylaminobenzoate (10287-53-3)	
STOT-single exposure	May cause respiratory irritation.
BisGMA (1565-94-2)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Ethyl 4-Dimethylaminobenzoate (10287-53-3)	
NOAEL (oral, rat, 90 days)	74 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.7 (Repeated Dose (28 Days) Toxicity (Oral))
Triethylene Glycol Dimethacrylate (109-16-0)	
LOAEC (inhalation, rat, gas, 90 days)	350 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:
NOAEL (oral, rat, 90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, gas, 90 days)	100 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available

D/E Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Hydroxyethyl Methacrylate (868-77-9)	
Viscosity, kinematic	6.4 mm ² /s (20 °C)
Ethyl 4-Dimethylaminobenzoate (10287-53-3)	
Viscosity, kinematic	Not applicable
Symptoms/effects	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

2-Hydroxyethyl Methacrylate (868-77-9)	
LC50 - Fish [1]	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oryzias latipes, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	380 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	836 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
Ethyl 4-Dimethylaminobenzoate (10287-53-3)	
LC50 - Fish [1]	1.9 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	4.5 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
EC50 72h - Algae [1]	2.8 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Semi-static system, Fresh water, Experimental value, GLP)
EC50 72h - Algae [2]	0.96 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
BisGMA (1565-94-2)	
LC50 - Fish [1]	0.537 mg/l Source: ECOSAR
Triethylene Glycol Dimethacrylate (109-16-0)	
LC50 - Fish [1]	16.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	72.8 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
LOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

D/E Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

2-Hydroxyethyl Methacrylate (868-77-9)

Persistence and degradability	Biodegradability in soil: no data available. Readily biodegradable in water.
-------------------------------	--

Ethyl 4-Dimethylaminobenzoate (10287-53-3)

Persistence and degradability	Not readily biodegradable in water.
-------------------------------	-------------------------------------

BisGMA (1565-94-2)

Persistence and degradability	Biodegradability in water: no data available.
-------------------------------	---

Triethylene Glycol Dimethacrylate (109-16-0)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

12.3. Bioaccumulative potential

2-Hydroxyethyl Methacrylate (868-77-9)

Partition coefficient n-octanol/water (Log Pow)	0.42 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
---	---

Bioaccumulative potential	Not bioaccumulative.
---------------------------	----------------------

Ethyl 4-Dimethylaminobenzoate (10287-53-3)

Partition coefficient n-octanol/water (Log Pow)	3.2 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
---	---

Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
---------------------------	--

BisGMA (1565-94-2)

Partition coefficient n-octanol/water (Log Pow)	4.94 (Estimated value)
---	------------------------

Bioaccumulative potential	No bioaccumulation data available.
---------------------------	------------------------------------

Triethylene Glycol Dimethacrylate (109-16-0)

Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
---	--

Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
---------------------------	--

12.4. Mobility in soil

2-Hydroxyethyl Methacrylate (868-77-9)

Surface tension	No data available in the literature
-----------------	-------------------------------------

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.164 - 0.708 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
--	--

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

Ethyl 4-Dimethylaminobenzoate (10287-53-3)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
--	---

Ecology - soil	Low potential for adsorption in soil.
----------------	---------------------------------------

Triethylene Glycol Dimethacrylate (109-16-0)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.89 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
--	---

D/E Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Triethylene Glycol Dimethacrylate (109-16-0)

Ecology - soil

Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable
Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not applicable

TDG
Transport hazard class(es) (TDG) : Not applicable

IMDG
Transport hazard class(es) (IMDG) : Not applicable

IATA
Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT
No data available

D/E Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Urethane Dimethacrylate	CAS-No. Proprietary	30 - 50%
-------------------------	---------------------	----------

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

2-Hydroxyethyl Methacrylate (868-77-9)

Listed on the Canadian DSL (Domestic Substances List)

Ethyl 4-Dimethylaminobenzoate (10287-53-3)

Listed on the Canadian DSL (Domestic Substances List)

BisGMA (1565-94-2)

Listed on the Canadian DSL (Domestic Substances List)

Triethylene Glycol Dimethacrylate (109-16-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Triethylene Glycol Dimethacrylate (109-16-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

D/E Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 07/11/2023

Full text of H-phrases	
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation

Indication of changes:			
Section	Changed item	Change	Comments
	Revision date	Added	
	Precautionary statements (GHS US)	Modified	
	Hazard statements (GHS US)	Modified	
	Signal word (GHS US)	Added	
	Supersedes	Added	
	Issue date	Removed	
2.1	GHS-US classification	Modified	
3	Composition/Information on ingredients	Modified	
4	Symptoms/effects	Modified	
5.2	Fire hazard	Removed	
6	Emergency procedures	Modified	
6	Methods for cleaning up	Modified	
7.1	Precautions for safe handling	Modified	
7.2	Storage conditions	Modified	
8.2	Eye protection	Modified	

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.