

# SAFETY DATA SHEET

Creation Date 24-Jan-2014

Revision Date 24-Jan-2014

Revision Number 1

## 1. Identification

**Product Name** Reagent Alcohol  
**Cat No. :** C4305  
**Synonyms** Denatured Ethyl alcohol  
**Recommended Use** Laboratory chemicals  
**Uses advised against** No Information available

### Details of the supplier of the safety data sheet

<b>Company</b> Richard Allan Scientific A Subsidiary of Thermo Fisher Scientific 4481 Campus Drive Kalamazoo, MI 49008 Tel: (800) 522-7270	<b>Emergency Telephone Number</b> Chemtrec US: (800) 424-9300 Chemtrec EU: 001 (202) 483-7616
---	---

## 2. Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Specific target organ toxicity (single exposure)	Category 1
Target Organs - Central nervous system (CNS), Optic nerve.	
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Kidney, Liver, spleen, Blood.	

### Label Elements

**Signal Word**  
Danger

### **Hazard Statements**

Highly flammable liquid and vapor  
May cause drowsiness or dizziness  
Causes damage to organs  
Causes damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Do not breathe dust/fume/gas/mist/vapors/spray  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Keep cool

**Response**

IF exposed: Call a POISON CENTER or doctor/physician

**Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell

**Skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

**Fire**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other hazards**

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous. WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

**Unknown Acute Toxicity**

.? % of the mixture consists of ingredients of unknown toxicity.

### 3. Composition / Information on ingredients

**Haz/Non-haz**

Component	CAS-No	Weight %
Isopropyl alcohol	67-63-0	4-6
Ethyl alcohol	64-17-5	89-91
Methyl alcohol	67-56-1	4-5

### 4. First-aid measures

#### 4. First-aid measures

<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
<b>Inhalation</b>	Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a respiratory medical device. Immediate medical attention is required.
<b>Ingestion</b>	Do not induce vomiting. Call a physician or Poison Control Center immediately.
<b>Most important symptoms/effects</b>	Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
<b>Notes to Physician</b>	Treat symptomatically.

#### 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	Carbon dioxide (CO <sub>2</sub> ). Dry chemical. Dry sand.. alcohol-resistant foam.
<b>Unsuitable Extinguishing Media</b>	Water may be ineffective
<b>Flash Point</b>	13.9°C / 57°F
<b>Method -</b>	No information available.
<b>Autoignition Temperature</b>	362.8°C / 685°F
<b>Explosion Limits</b>	
<b>Upper</b>	19 vol %
<b>Lower</b>	3.3 vol %
<b>Sensitivity to mechanical impact</b>	No information available.
<b>Sensitivity to static discharge</b>	No information available.

#### Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

**Hazardous Combustion Products** Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Formaldehyde.

#### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

#### NFPA

**Health**  
3

**Flammability**  
3

**Instability**  
0

**Physical hazards**  
N/A

#### 6. Accidental release measures

<b>Personal Precautions</b>	Remove all sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing.
<b>Environmental Precautions</b>	See Section 12 for additional ecological information.
<b>Methods for Containment and Clean Up</b>	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

## 7. Handling and storage

### Handling

Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharges. Use only under a chemical fume hood. Do not breathe vapors/dust. Do not get in eyes, on skin, or on clothing. Do not ingest.

### Storage

Keep away from open flames, hot surfaces and sources of ignition. Flammables area.

## 8. Exposure controls / personal protection

### Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 980 mg/m <sup>3</sup> (Vacated) STEL: 500 ppm (Vacated) STEL: 1225 mg/m <sup>3</sup> TWA: 400 ppm TWA: 980 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm (Vacated) TWA: 1900 mg/m <sup>3</sup> TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m <sup>3</sup> (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m <sup>3</sup> Skin TWA: 200 ppm TWA: 260 mg/m <sup>3</sup>	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup>

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Isopropyl alcohol	TWA: 400 ppm TWA: 985 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1230 mg/m <sup>3</sup>	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 400 ppm
Ethyl alcohol	TWA: 1000 ppm TWA: 1880 mg/m <sup>3</sup>	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>	STEL: 1000 ppm
Methyl alcohol	TWA: 200 ppm TWA: 262 mg/m <sup>3</sup> STEL: 250 ppm STEL: 328 mg/m <sup>3</sup> Skin	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 310 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 250 ppm Skin

### Legend

**ACGIH** - American Conference of Industrial Hygiene

**OSHA** - Occupational Safety and Health Administration

**NIOSH IDLH**: Immediately Dangerous to Life or Health

### Engineering Measures

Use explosion-proof electrical/ventilating/lighting/equipment. Use only under a chemical fume hood.

### Personal Protective Equipment

#### Eye/face Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166

#### Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure

<b>Respiratory Protection</b>	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
<b>Hygiene Measures</b>	Handle in accordance with good industrial hygiene and safety practice

## 9. Physical and chemical properties

<b>Physical State</b>	Liquid
<b>Appearance</b>	Clear
<b>Odor</b>	aromatic
<b>Odor Threshold</b>	No information available.
<b>pH</b>	No information available.
<b>Melting Point/Range</b>	-114.1°C / -173.4°F
<b>Boiling Point/Range</b>	78.5°C / 173.3°F
<b>Flash Point</b>	13.9°C / 57°F
<b>Evaporation Rate</b>	No information available.
<b>Flammability (solid,gas)</b>	No information available.
<b>Flammability or explosive limits</b>	
Upper	19 vol %
Lower	3.3 vol %
<b>Vapor Pressure</b>	mmHg @ 44 mmHg °F
<b>Vapor Density</b>	1.24
<b>Relative Density</b>	0.8
<b>Solubility</b>	Soluble in water
<b>Partition coefficient; n-octanol/water</b>	No data available
<b>Autoignition Temperature</b>	362.8°C / 685°F
<b>Decomposition temperature</b>	No information available.
<b>Viscosity</b>	No information available.

## 10. Stability and reactivity

<b>Reactive Hazard</b>	None known, based on information available.
<b>Stability</b>	Stable under normal conditions.
<b>Conditions to Avoid</b>	Heat, flames and sparks.
<b>Incompatible Materials</b>	Strong oxidizing agents, Peroxides, Acids, Heavy metals
<b>Hazardous Decomposition Products</b>	Carbon monoxide (CO), Carbon dioxide (CO <sub>2</sub> ), Formaldehyde
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur
<b>Hazardous Reactions</b>	None under normal processing

## 11. Toxicological information

### Acute Toxicity

<b>Oral LD50</b>	Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.
<b>Dermal LD50</b>	Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.
<b>Vapor LC50</b>	Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl alcohol	5840 mg/kg ( Rat )	13900 mg/kg ( Rat ) 12870 mg/kg ( Rabbit )	72.6 mg/L ( Rat ) 4 h
Ethyl alcohol	7060 mg/kg ( Rat )	Not listed	20000 ppm/10H ( Rat )

Methyl alcohol	5628 mg/kg ( Rat )	15800 mg/kg ( Rabbit )	64000 ppm ( Rat ) 4 h 83.2 mg/L ( Rat ) 4 h
----------------	--------------------	------------------------	--

**Toxicologically Synergistic Products** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Irritation** Irritating to eyes

**Sensitization** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Isopropyl alcohol	67-63-0	Not listed	Not listed	Not listed	Not listed	Not listed
Ethyl alcohol	64-17-5	Group 1	Not listed	A3	X	Not listed
Methyl alcohol	67-56-1	Not listed	Not listed	Not listed	Not listed	Not listed

**Mutagenic Effects** Mutagenic effects have occurred in humans.

**Reproductive Effects** Adverse reproductive effects have occurred in humans..

**Developmental Effects** Substances known to cause developmental toxicity in humans.

**Teratogenicity** Teratogenic effects have occurred in humans..

**STOT - single exposure** Central nervous system (CNS), Optic nerve.

**STOT - repeated exposure** Kidney, Liver, spleen, Blood.

**Aspiration hazard** No information available.

**Symptoms / effects, both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Endocrine Disruptor Information** No information available

**Other Adverse Effects** Teratogenic effects have occurred in experimental animals.. See actual entry in RTECS for complete information.

## 12. Ecological information

### Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Isopropyl alcohol	1000 mg/L EC50 > 72 h 1000 mg/L EC50 > 96 h	1400000 µg/L LC50 96 h 9640 mg/L LC50 96 h 11130 mg/L LC50 96 h	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h
Ethyl alcohol	EC50 (72h) = 275 mg/l (Chlorella vulgaris)	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h	Photobacterium phosphoreum:EC50 = 34634 mg/L/30 min Photobacterium phosphoreum:EC50 = 35470 mg/L/5 min	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h
Methyl alcohol	Not listed	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	EC50 > 10000 mg/L 24h

**Persistence and Degradability** No information available.

**Bioaccumulation/ Accumulation** No information available

**Mobility** .

Component	log Pow
Isopropyl alcohol	0.05
Ethyl alcohol	-0.32
Methyl alcohol	-0.74

### 13. Disposal considerations

**Waste Disposal Methods** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	-

### 14. Transport information

**DOT**

UN-No UN1170  
 Proper Shipping Name ETHANOL SOLUTION  
 Hazard Class 3  
 Packing Group II

**TDG**

UN-No UN1170  
 Proper Shipping Name ETHANOL SOLUTION  
 Hazard Class 3  
 Packing Group II

**IATA**

UN-No UN1170  
 Proper Shipping Name ETHANOL SOLUTION  
 Hazard Class 3  
 Packing Group II

**IMDG/IMO**

UN-No UN1170  
 Proper Shipping Name ETHANOL SOLUTION  
 Hazard Class 3  
 Packing Group II

### 15. Regulatory information

**International Inventories**

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	CHINA	KECL
Isopropyl alcohol	X	X	-	200-661-7	-		X	X	X	X	X
Ethyl alcohol	X	X	-	200-578-6	-		X	X	X	X	X
Methyl alcohol	X	X	-	200-659-6	-		X	X	X	X	X

**Legend:**

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.  
 N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.  
 P - Indicates a commenced PMN substance  
 R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.  
 S - Indicates a substance that is identified in a proposed or final Significant New Use Rule  
 T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.  
 XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).  
 Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.  
 Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

**U.S. Federal Regulations**

**TSCA 12(b)** Not applicable

**SARA 313**

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Isopropyl alcohol	67-63-0	5.5	1.0
Methyl alcohol	67-56-1	4.5	1.0

**SARA 311/312 Hazardous Categorization**

Acute Health Hazard Yes  
 Chronic Health Hazard Yes  
 Fire Hazard Yes  
 Sudden Release of Pressure Hazard No  
 Reactive Hazard No

**Clean Water Act** Not applicable

**Clean Air Act**

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-

**OSHA - Occupational Safety and Health Administration**

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Methyl alcohol	5000 lb	-

**California Proposition 65** This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65	Prop 65 NSRL
Ethyl alcohol	64-17-5	Developmental	-
Methyl alcohol	67-56-1	Methanol	-

**State Right-to-Know**

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Isopropyl alcohol	X	X	X	-	X
Ethyl alcohol	X	X	X	-	X
Methyl alcohol	X	X	X	X	X



**U.S. Department of Transportation**

Reportable Quantity (RQ): Y  
DOT Marine Pollutant N  
DOT Severe Marine Pollutant N

**U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

**Other International Regulations**

**Mexico - Grade** Serious risk, Grade 3

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**WHMIS Hazard Class** B2 Flammable liquid  
D1B Toxic materials  
D2A Very toxic materials

**16. Other information**

**Prepared By** Regulatory Affairs  
Richard Allan Scientific  
A Subsidiary of Thermo Fisher Scientific  
Tel: (800) 522-7270

**Creation Date** 24-Jan-2014  
**Revision Date** 24-Jan-2014  
**Print Date** 24-Jan-2014  
**Revision Summary** "\*\*\*\*", and red text indicates revision

**Disclaimer**

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of SDS**