

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 6/13/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : Cytology Fixative Product code : 400631, 400632

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only

For professional use only

Restrictions on use : Not for food, drug or household use

1.3. Supplier

EDM 3, LLC

3611 St Johns Bluff Road, Suite 1

Jacksonville, FL 32224

T 800-638-2625, Monday-Friday: 8:00 AM-5:00 PM

1.4. Emergency telephone number

Emergency number : INFOTRAC at 1-800-535-5053 (Domestic within the USA and Canada) or 1-352-323-3500

(International callers may call collect), 24 hours/day, 7 days/week.

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2

Serious eye damage/eye irritation Category 2

Specific target organ toxicity – Single exposure, Category 3, Narcosis

H225

H319

Causes serious eye irritation

May cause drowsiness or dizziness

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.
P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a poison center or doctor if you feel unwell.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.	GHS US classification
isopropanol (2-propanol)	CAS-No.: 67-63-0	70	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 Aquatic Chronic 4, H413
acetone	CAS-No.: 67-64-1	20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Water	CAS-No.: 7732-18-5	≈ 9	Not classified
polyethylene glycol	CAS-No.: 25322-68-3	≈ 1	Not classified

Full text of hazard classes and H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general

First-aid measures after inhalation

First-aid measures after skin contact

First-aid measures after eye contact

- Call a poison center/doctor/physician if you feel unwell.
- Remove person to fresh air and keep comfortable for breathing.
- Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
- Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to
- do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

: Call a poison center/doctor/physician if you feel unwell. First-aid measures after ingestion

6/13/2024 (Issue date) US - en 2/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is

expected to be an inhalation hazard.

Symptoms/effects after skin contact : None under normal conditions.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor. Explosion hazard : No direct explosion hazard.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb

spillage to prevent material-damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent

migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

6/13/2024 (Issue date) US - en 3/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only

outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid

contact with skin and eyes.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Ground/bond container and receiving equipment.

Storage conditions

: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Packaging materials

Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

isopropanol (2-propanol) (67-63-0)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	200 ppm	
ACGIH OEL STEL	400 ppm	
acetone (67-64-1)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	250 ppm	
ACGIH OEL STEL	500 ppm	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:	
Protective gloves	
Eye protection:	
Safety glasses	

6/13/2024 (Issue date) US - en 4/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Explosive properties





SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance Colorless liquid. Color No data available Odor Alcohol odour Odor threshold No data available : No data available рΗ Melting point : Not applicable Freezing point : No data available Boiling point No data available Flash point No data available Relative evaporation rate (butyl acetate=1) No data available Flammability (solid, gas) No data available Vapor pressure No data available Relative vapor density at 20°C No data available Relative density No data available Solubility No data available Partition coefficient n-octanol/water (Log Pow) : No data available : No data available Auto-ignition temperature Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** : No data available

Oxidizing properties :	No data available
isopropanol (2-propanol)	
Boiling point	83 °C (1013 hPa)
Flash point	12 °C (Closed cup)
Auto-ignition temperature	399 °C (T2)
Vapor pressure	44 hPa (20 °C)
Vapor pressure at 50°C	236 hPa (Antoine equation)

No data available

acetone	
Boiling point	56 °C
Flash point	-17 °C (Closed cup)
Auto-ignition temperature	465 °C (T1)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

acetone	
Vapor pressure	240 hPa (20 °C)
Vapor pressure at 50°C	828 hPa

polyethylene glycol	
Boiling point	870 °C (975 hPa)
Flash point	171 – 260 °C
Vapor pressure	< 0.01 hPa (20 °C)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

isopropanol (2-propanol) (67-63-0)	
LD50 oral rat	5840 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	16400 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

isopropanol (2-propanol) (67-63-0)		
ATE US (oral)	5840 mg/kg body weight	
ATE US (dermal)	12890400 mg/kg body weight	
acetone (67-64-1)		
LD50 oral rat	5800 mg/kg (Rat, Female, Experimental value, Oral, 14 day(s))	
LD50 dermal rabbit	> 15800 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))	
LC50 Inhalation - Rat	132 mg/l (3 h, Rat, Male, Experimental value, Inhalation (vapours))	
ATE US (oral)	5800 mg/kg body weight	
ATE US (vapors)	132 mg/l/4h	
ATE US (dust, mist)	132 mg/l/4h	
polyethylene glycol (25322-68-3)		
LD50 oral rat	30200 mg/kg (Rat, Literature study, Oral)	
LD50 dermal rabbit	> 20000 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal)	
ATE US (oral)	30200 mg/kg body weight	
Skin corrosion/irritation :	Not classified	
isopropanol (2-propanol) (67-63-0)		
рН	No data available in the literature	
acetone (67-64-1)		
рН	5 – 6 (20 °C)	
polyethylene glycol (25322-68-3)		
рН	3 – 4.45 (1 %, 25 °C)	
Serious eye damage/irritation :	Causes serious eye irritation.	
isopropanol (2-propanol) (67-63-0)		
рН	No data available in the literature	
acetone (67-64-1)		
рН	5 – 6 (20 °C)	
polyethylene glycol (25322-68-3)		
рН	3 – 4.45 (1 %, 25 °C)	
, ,	Not classified	
3 ,	Not classified Not classified	
	NOL Classified	
isopropanol (2-propanol) (67-63-0) IARC group	3 - Not classifiable	
	Not classified	
	May cause drowsiness or dizziness.	
isopropanol (2-propanol) (67-63-0)		
STOT-single exposure	May cause drowsiness or dizziness.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure :	Not classified
Aspiration hazard :	Not classified
Viscosity, kinematic :	No data available
isopropanol (2-propanol) (67-63-0)	
Viscosity, kinematic	2.66 mm²/s (25 °C, Estimated value)
acetone (67-64-1)	
Viscosity, kinematic	No data available in the literature
Symptoms/effects :	May cause drowsiness or dizziness.
Symptoms/effects after inhalation :	Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact :	None under normal conditions.
Symptoms/effects after eye contact :	Eye irritation.
Symptoms/effects after ingestion :	None under normal conditions.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

	enects in the environment.	
isopropanol (2-propanol) (67-63-0)		
LC50 - Fish [1]	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)	
acetone (67-64-1)		
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)	
polyethylene glycol (25322-68-3)		
LC50 - Fish [1]	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Poecilia reticulata, Static system, Fresh water, Experimental value, Nominal concentration)	
LC50 - Other aquatic organisms [1]	> 1000 mg/l (96 h)	

12.2. Persistence and degradability

Cytology Fixative		
Persistence and degradability	Not rapidly degradable	
isopropanol (2-propanol) (67-63-0)		
Persistence and degradability	Biodegradable in the soil, Biodegradable in the soil under anaerobic conditions, Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	1.19 g O ₂ /g substance	
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance	
ThOD	2.4 g O ₂ /g substance	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

acetone (67-64-1)		
Persistence and degradability	Biodegradable in the soil, Biodegradable in the soil under anaerobic conditions, Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance	
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance	
ThOD	2.2 g O ₂ /g substance	
polyethylene glycol (25322-68-3)		
Persistence and degradability	Readily biodegradable in water.	
Water (7732-18-5)		
Persistence and degradability	Not rapidly degradable	

12.3. Bioaccumulative potential

isopropanol (2-propanol) (67-63-0)		
BCF - Fish [1]	1015 (BCFBAF v3.01, Estimated value)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
acetone (67-64-1)		
BCF - Fish [1]	0.69 (Pisces, Literature study)	
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
polyethylene glycol (25322-68-3)		
BCF - Fish [1]	3.2 (Other, Pisces, Calculated value)	
Partition coefficient n-octanol/water (Log Pow)	-0.96 – -0.7 (Weight of evidence approach, Other, 30 °C)	
Bioaccumulative potential	Not bioaccumulative.	

12.4. Mobility in soil

isopropanol (2-propanol) (67-63-0)		
Surface tension	No data available (test not performed)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Ecology - soil	Highly mobile in soil.	
acetone (67-64-1)		
Surface tension	23.3 mN/m (20 °C)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Ecology - soil	Highly mobile in soil.	
polyethylene glycol (25322-68-3)		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1 (log Koc, Other, Calculated value)	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

polyethylene glycol (25322-68-3)

Ecology - soil Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations. Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Flammable vapors may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

UN-No.(DOT) : UN1219 UN-No. (TDG) : UN1219 UN-No. (IMDG) : 1219 UN-No. (IATA) : 1219

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Isopropyl alcohol Proper Shipping Name (TDG) : ISOPROPANOL

Proper Shipping Name (IMDG) : ISOPROPANOL (ISOPROPYL ALCOHOL)

Proper Shipping Name (IATA) : Isopropanol

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3 Hazard labels (DOT) : 3



TDG

Transport hazard class(es) (TDG) : 3 Hazard labels (TDG) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Hazard labels (IMDG) : 3

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : II
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1219

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110

kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature

during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 4b;150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 5 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

TDG

UN-No. (TDG) : UN1219

Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E2
Passenger Carrying Road Vehicle or Passenger : 5 L

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 129

IMDG

Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2

6/13/2024 (Issue date) US - en 11/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS

EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS

Stowage category (IMDG) : B Flash point (IMDG) : 12°C c.c.

Properties and observations (IMDG) : Colourless, mobile liquid. Flashpoint: 12°C c.c. Explosive limits: 2% to 12%. Miscible with water.

IATA

PCA Excepted quantities (IATA) : E2 PCA Limited quantities (IATA) : Y341 PCA limited quantity max net quantity (IATA) : 1L PCA packing instructions (IATA) : 353 : 5L PCA max net quantity (IATA) CAO packing instructions (IATA) : 364 CAO max net quantity (IATA) : 60L Special provision (IATA) : A180 ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

acetone	CAS-No. 67-64-1	20%
polyethylene glycol	CAS-No. 25322-68-3	≈ 1%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2-propanol CAS-No. 67-63-0 70%

15.2. International regulations

CANADA

isopropanol (2-propanol) (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

isopropanol (2-propanol) (67-63-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Water (7732-18-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
isopropanol (2-propanol)(67-63-0)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H413	May cause long lasting harmful effects to aquatic life


NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can

be ignited under almost all ambient temperature conditions.

NFPA reactivity: 0 - Material that in themselves are normally stable, even under fire

 0 - Material that in themselves are normally stable, even under fire conditions.



Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. EDM3 shall not be liable for any damage resulting from handling.