



eki-chem.com

SAFETY DATA SHEET

Revision Date 18-Nov-2022

Version 5

1. IDENTIFICATION

Product Name Methyl Alcohol
Product Code 5865
CAS No. 67-56-1
Synonyms Methanol
Chemical Formula CH₃OH
Recommended Use For laboratory, scientific, R&D or manufacturing use.
Company E K Industries, Inc.
1403 Herkimer St.
Joliet, IL 60432
Tel. (800) 283-4244
Emergency Telephone Call CHEMTREC 1-800-424-9300 (EKI CCN 7453)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 3
Acute toxicity - Dermal	Category 3
Acute toxicity - Inhalation (Dusts/Mists)	Category 3
Specific target organ toxicity (single exposure)	Category 1
Flammable liquids	Category 2

Label elements

Signal word

Danger

Hazard statements

Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled. Causes damage to organs.
Highly flammable liquid and vapor.



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe

dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting/equipment. Keep cool.

Precautionary Statements - Response

IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
Avoid breathing vapors or mists. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse mouth.
In case of fire: Use CO2, dry chemical, or foam for extinction. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
Prevent entry into waterways, sewers, basements or confined areas.

Precautionary Statements - Storage

Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

3. COMPOSITION/INFORMATION ON INGREDIENTS

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Chemical Name	CAS No.	Weight-%
Methyl alcohol	67-56-1	100

4. FIRST AID MEASURES

Description of first aid measures

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Seek immediate medical attention/advice.

Skin contact Wash thoroughly with soap and water while removing contaminated garments. Get medical attention if irritation develops. Get medical attention if irritation develops and persists.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion Do NOT induce vomiting unless instructed to do so by medical personnel. If conscious, rinse mouth and give several glasses of water to drink. Never give anything by mouth to an unconscious person. Get immediate medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms Causes skin and eye irritation. If swallowed or inhaled, causes irritation. Intoxicant. May cause headache, drowsiness, nausea, vomiting, blurred vision, blindness, coma, and death.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water spray (fog) CO2, dry chemical, alcohol-resistant foam.

Large Fire In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use CO2, dry chemical, or foam to extinguish.

Specific hazards arising from the chemical

Vapors can flow along surfaces to distant ignition sources and flash back. May form explosive mixtures with air.

Hazardous combustion products

Carbon dioxide (CO2).

Protective equipment and precautions for firefighters

Firefighters should wear self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode.

NFPA Health hazards 1 Flammability 3 Instability 0 **Physical and Chemical Properties -**

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Take precautionary measures against static discharges. Ensure adequate ventilation, especially in confined areas. Wear protective gloves/protective clothing and eye/face protection.

Environmental precautions Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Absorb spill with inert material, scoop up and containerize for disposal.

7. HANDLING AND STORAGE

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Store in an approved Flammable Liquids storage area.

Incompatible materials Strong oxidizing agents. Aluminum. Zinc.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl alcohol 67-56-1	STEL: 250 ppm TWA: 200 ppm Skin	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) Skin	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³

Appropriate engineering controls

Engineering Controls Emergency showers, eyewash stations, ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear protective gloves and protective clothing. Wear fire/flammable resistant/retardant clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Clear, colorless
Odor	Characteristic
Odor threshold	No Data Available
pH	No Data Available
Melting point / freezing point	-98 C
Boiling point / boiling range	64.5 C
Flash point	12 C
Evaporation rate	No Data Available
Flammability (solid, gas)	No Data Available
Flammability Limit in Air	
Upper flammability limit:	36%
Lower flammability limit:	6%
Vapor pressure	No Data Available
Vapor density	No Data Available
Relative density	No Data Available
Water solubility	Miscible with water
Solubility in other solvents	No Data Available
Partition coefficient	No Data Available
Autoignition temperature	464 C
Decomposition temperature	No Data Available
Kinematic viscosity	No Data Available

10. STABILITY AND REACTIVITY

Stability Stable under recommended storage conditions.

Possibility of Hazardous Reactions Risk of explosion with oxidizing agents, perchlorates, nitrogen oxides, halogens, hydrogen peroxide, nitric acid.

Conditions to avoid Extremes of temperature and direct sunlight. Sources of ignition.

Incompatible materials Strong oxidizing agents. Aluminum. Zinc.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO₂). Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Toxic by inhalation.

Eye contact No data available.

Skin contact Toxic in contact with skin.

Ingestion Toxic if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl alcohol 67-56-1	= 6200 mg/kg (Rat)	= 15800 mg/kg (Rabbit) = 15840 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No Data Available.
Germ cell mutagenicity No Data Available.
Carcinogenicity This chemical does not contain any carcinogens or potential carcinogens as listed by ACGIH, OSHA, IARC or NTP
STOT - single exposure
 - Respiratory system
 - Central nervous system
 - Optic nerve

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Methyl alcohol 67-56-1	-	19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static	-

Persistence and degradability

No Data Available.

Bioaccumulation

No Data Available.

Chemical Name	Partition coefficient
Methyl alcohol 67-56-1	-0.77

Other adverse effects

No Data Available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Do not reuse container. Emptied containers may contain residue. Continue to follow label warnings after container is emptied.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl alcohol 67-56-1	-	Included in waste stream: F039	-	U154

Chemical Name	California Hazardous Waste Status
Methyl alcohol 67-56-1	Toxic Ignitable

14. TRANSPORT INFORMATION

Transportation information is provided as a general reference only and may not be applicable in all situations. This information applies to non-bulk shipments only. Per 49 CFR §173.22, it is the shipper's responsibility to ensure that all materials are properly packaged, classified and labeled prior to shipment.

DOT

UN/ID no. UN1230
 Proper shipping name Methanol
 Hazard Class 3
 Packing Group II
 Reportable Quantity (RQ) 5000 lbs

IATA

UN/ID no. UN1230
 Proper shipping name Methanol
 Hazard Class 3
 Subsidiary hazard class 6.1
 Packing Group II

15. REGULATORY INFORMATION

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Methyl alcohol - 67-56-1	1.0

SARA 311/312 Hazard Categories

Acute health hazard No
 Chronic Health Hazard No
 Fire hazard No
 Sudden release of pressure hazard No
 Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methyl alcohol 67-56-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
---------------	---------------------------

Methyl alcohol - 67-56-1	Developmental
--------------------------	---------------

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Methyl alcohol 67-56-1	X	X	X

16. OTHER INFORMATION

Prepared By EKI Regulatory Affairs (Email: reg@eki-chem.com)
Revision Date 18-Nov-2022

Disclaimer

E K Industries, Inc. makes no representation as to the comprehensiveness or accuracy of this document. Individuals using this information, or the product to which it refers, must exercise their independent judgment in determining all appropriateness for a particular purpose. Accordingly, E K Industries, Inc. will not be responsible for damages of any kind or nature resulting from the use of this information or the corresponding product. No representations or warranties of any kind or nature, including but not limited to: express warranties, implied warranties or merchantability, or warranties of fitness for a particular purpose, are made hereunder with respect to the information set forth herein or to the product to which the information refers.

End of Safety Data Sheet