# Heraeus Kulzer

Mitsui Chemicals Group

# **SAFETY DATA SHEET**

Product identifier used on the la					
Product Name: Product Code:		K-3 Plaster and	Stone Remover		
Product Code: MSDS Manufacturer Number:	50036206, D002	50036206CN			
Other means of Identification: Synonyms:	Not applica	Not applicable			
<u>Recommended use of the chem</u> Product Use/Restriction:			ultrasonic deaner.		
Chemical manufacturer address	and telephone number:				
Manufacturer Name:	Heraeus Ku		Chemicals Group)		
Address:	300 Heraeu South Bend	us Way 1, Indiana 46614-	2517		
General Phone Number:	USA	USA 800-431-1785			
General Phone Number:	600-431-1	/00			
Emergency phone number: Emergency Phone Number:	Chamtrac	@ 1-800-424-930			
bhergency Phone Number.	Chemiter	₩ 1-000-424-930	1		
ECTION 2 : HAZARD(S) IDE	ENTIFICATION				
<u>Classification of the chemical in</u>	accordance with Å61910.12	200(d)(f):			
Signal Word:	Not applicable.				
GHS Class:		urdous according t	o OSHA Hazard Communication Star	dard, 29 CFR 1910,1200	
Hazard Statements: None.					
Precautionary Statements: None.					
Unanado anti all'antica da attra	· · · · · · · · · · · · · · · · · · ·				
Hazards not otherwise classified			cation process:		
Route of Exposure:	Eyes. Skin, Inhalation	i. Ingestion.			
Potential Health Effects:					
Eye:	May cause irritation.				
Skin:	May cause initation.				
Inhalation:	Prolonged or excessiv	/e inhalation may	cause respiratory tract irritation.		
Ingestion:	Ingestion can cause g	gastroIntestinal in	itation, nausea, vomiting and diarrh	eal	
Target Organs:	Eyes. Skin. Respirator	ry system. Digest	ve system.		
ECTION 3 : COMPOSITION	INFORMATION ON ING	REDIENTS			
Mixtures:					
hemical Name		CAS#	Ingredient Percent	EC Num.	
atrasodlum Ethylenedlamine tet	ra acetic acid (EDTA)	64-02-8	1 - 5 by weight		
Notes :			uct aré non-hazardous or are in a si	nall enough quantity as t	
	not meet regulatory th	nresholas for aisc	osure.		
ECTION 4 : FIRST AID MEA	SURES				
Description of necessary measu	res;				
Eye Contact:	If symptome doubles	Ringe caullouch	with water for several minutes. Rem	ave contact longer 15	

Skin Contact:	If symptoms develop. Wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
Inhalation:	If symptoms persist, call a physician.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

# SECTION 5 : FIRE FIGHTING MEASURES

#### Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media:	Use dry chemical or foam when fighting fires involving this material. Water mist may be used to cool closed containers.	
Special protective equipment and p	precautions for fire-fighters:	
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.	
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.	
NFPA Ratings:		
NFPA Health:	1	
NFPA Flammability:	i	

#### SECTION 6 : ACCIDENTAL RELEASE MEASURES

0

NFPA Reactivity:

Personal precautions, protective equipment and emergency procedures:					
Personnel Precautions: For large spills Evacuate area and keep unnecessary and unprotected personnel from entering the area.					
Environmental precautions:					
Environmental Precautions: For large spills Avoid runoff into storm sewers, ditches, and waterways.					
Methods and materials for containment and deaning up:					
Methods for containment: For large spills Contain spills with an inert absorbent material such as soil, sand or oil dry.					
Methods for deanup: For large spills Place into a suitable container for disposal.					

## SECTION 7 : HANDLING and STORAGE

Precautions for safe handling:					
Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.				
Hygiene Practices:	Wash thoroughly after handling. Avoid contact with eyes.				
Special Handling Procedures:	Do not re-use empty containers.				
Conditions for safe storage, including any incompatibilities:					
Storage: Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Kee container tightly closed when not in use.					

## SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Dri Claup WC2 Director and Stone Domains	Product Code: D002
Respiratory Protection:	No special protective equipment required under normal conditions of use. No personal respiratory protective equipment normally required. The need for
Skin Protection Description:	No special protective equipment required under normal conditions of use.
Eye/Face Protection:	No special protective equipment required under normal conditions of use. If splashes are likely to occur, wear: Chemical splash goggles.
Individual protection measures:	
Engineering Controls:	No special protective equipment required under normal conditions of use. Use appropriate engineering control such as process endosures, local exhaust ventilation, or other engineering controls to control airbome levels below recommended exposure limits. Good general ventilation should be sufficient to control airbome levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Appropriate engineering controls:	
EXPOSURE GUIDELINES:	

Dri-Clave VK-3 Plaster and Stone Remover Revision:: 5/1/2015

#### PPE Pictograms:



## SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

#### PHYSICAL AND CHEMICAL PROPERTIES:

Physical State:	Liquid.
Color:	Transparent pink
Odor:	Odorless.
Odor Threshold:	Not determined.
Boiling Point:	215°C (419) °F
Melting Point:	Not determined.
Specific Gravity:	1.09 (Ref: water = 1).
Solubility:	Very soluble.
Vapor Density:	Not determined.
Vapor Pressure:	Not determined.
Percent Volatile:	88%
Evaporation Rate:	Not determined.
pH:	13.3 - 13.6
Viscosity:	Not determined.
Coefficient of Water/Oll Distribution:	Not determined.
Flammability:	Not determined.
Flash Point:	210 °F (99°C)
Flash Point Method:	Tag Closed Cup (T.C.C)
Lower Flammable/Explosive Limit:	Not determined.
Upper Flammable/Explosive Limit:	Not determined.
Auto Ignition Temperature:	Not determined.
Oxidizing Properties:	Not determined.
VOC Content:	Not determined.

## SECTION 10 : STABILITY and REACTIVITY

Chemical Stability:	
Chemical Stability:	Stable under recommended handling and storage conditions.
Possibility of hazardous reactions:	
Hazardous Polymerization:	Will not occur.
Conditions To Avoid:	
Conditions to Avoid:	Avoid contact with Incompatible materials,
Incompatible Materials:	
Incompatible Materials:	Strong acids.

## SECTION 11 : TOXICOLOGICAL INFORMATION

## TOXICOLOGICAL INFORMATION:

Eye:	Administration into the eye - Rabbit Standard Draize test; 1900 ug [Not reported.] Administration into the eye - Rabbit Standard Draize test; 100 mg/24H [Moderate] (RTECS)
Ingestion:	Oral - Rat LD50 - Lethal dose, 50 percent kill: 10 gm/kg [Details of toxic effects not reported othe than lethal dose value] (RTECS)

# SECTION 12 : ECOLOGICAL INFORMATION

# Ecotoxicity:

Ecotoxicity:

No environmental Information found for this product.

Notes

Canada DSL:

Description of waste:	
Vaste Disposal:	Dispose of in accordance with Local, State, Federal and Provincial regulations,

#### SECTION 14 : TRANSPORT INFORMATION

The data provided in this section is for information only. Please apply the appropriate regulations to properly classify your shipment.

#### SECTION 15 ; REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:					
TSCA Inventory Status:	Status: All the constituents of this product are TSCA listed or exempt from listing.				
SARA:	This product does not contain any chemicals which are subject to the reporting requirements of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III (40CFR, Part 372).				
California PROP 65:	The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This product does not contain any Proposition 65 chemicals.				
Tetrasodium Ethylenediamine tet	ra acetic acid (EDTA):				
TSCA Inventory Status:	Listed				

SECTION	16	1	ADDITIONAL	INFORMATION

Listed

HMIS Health Hazard:	1
HMIS Fire Hazard:	1
HMIS Reactivity:	0
HMIS Personal Protection:	x
Other Information:	HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). The customer is responsible for determining the appropriate PPE to be used for

Association (NPCA). The customer is responsible for determining the appropriate PPE to be used for the task. The National Fire Protection Association (NFPA) rating system is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. NFPA hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. NFPA hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. The NFPA system is intended to be interpreted and applied only by properly trained individuals to identify fire, health, and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are dassified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.



May 01, 2015 Supercedes MSDS 2/11/2013 Regulatory department

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.