

Page 1/10

Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

1 Identification Product identifier

· Trade name: Cuttersil Hardener Universal Plus liquid

· Application of the substance / the mixture Activator for dental impression material

· Details of the supplier of the safety data sheet

• **Manufacturer/Supplier:** Kulzer GmbH Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

- Information department: Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545 e-mail: customer.servicehkna@kulzer-dental.com
- Emergency telephone number: Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapor.
Acute Tox. 3 H331 Toxic if inhaled.
Eye Irrit. 2A H319 Causes serious eye irritation.
STOT SE 3 H335 May cause respiratory irritation.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

Hazard-determining components of labeling: tetraethyl orthosilicate dioctyltin oxide tetramethyl orthosilicate
Hazard statements Flammable liquid and vapor. Toxic if inhaled. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.

Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. Do not breathe dust/fume/gas/mist/vapors/spray.

(Contd. on page 2)

USA



Page 2/10

Safety Data Sheet acc. to OSHA HCS





Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Page 3/10

(Contd. of page 2)

Trade name: Cuttersil Hardener Universal Plus liquid

· Information for doctor

• Most important symptoms and effects, both acute and delayed No further relevant information available.

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents Water with full jet.

Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
 - · Protective equipment: Mount respiratory protective device.
- · Additional information -

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water. Do not allow to penetrate the ground/soil.
 Methods and material for containment and cleaning up:
- Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues). Send for recovery or disposal in suitable receptacles.
- **Reference to other sections** See Section 13 for disposal information. See Section 8 for information on personal protection equipment.

7 Handling and storage

· Handling

- **Precautions for safe handling** Keep receptacles tightly sealed.
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Please observe the additional instructions in the product's instructions for use.
- Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.

(Contd. on page 4)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Cuttersil Hardener Universal Plus liquid

(Contd. of page 3)

Page 4/10

Conditions for safe storage, including any incompatibilities
 Storage

- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Store in dry conditions.
- Store receptacle in a well ventilated area.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

Control parameters

· Components with limit values that require monitoring at the workplace:

- 78-10-4 tetraethyl orthosilicate
- PEL 850 mg/m³, 100 ppm
- REL 85 mg/m³, 10 ppm
- TLV 85 mg/m³, 10 ppm

681-84-5 tetramethyl orthosilicate

- REL 6 mg/m^3 , 1 ppm
- TLV 6 mg/m^3 , 1 ppm

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- Personal protective equipment
 - General protective and hygienic measures
 - Avoid contact with the eyes.
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all solled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Do not inhale gases / fumes / aerosols.
 - Avoid contact with the eyes and skin.
 - · Breathing equipment: Not required.
 - Protection of hands:
 - Impervious gloves
 - Check protective gloves prior to each use for their proper condition. recommended
 - Material of gloves
 - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
 - Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



Page 5/10

Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Cuttersil Hardener Universal Plus liquid

- (Contd. of page 4) For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Butyl rubber, BR Nitrile rubber, NDD
 - Nitrile rubber, NBR

• Eye protection: Safety glasses • Body protection: Protective work clothing.

Information on basic physical and chemical properties · General Information	
· Appearance:	
Form:	Fluid Red
· Color: · Odor:	Aromatic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
 Melting point/Melting range: 	undetermined
 Boiling point/Boiling range: 	110 °C (230 °F)
· Flash point:	> 48 °C (> 118 °F)
· Flammability (solid, gaseous)	Not applicable.
· Ignition temperature:	345 °C (653 °F)
 Decomposition temperature: 	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
 Vapor pressure at 20 °C (68 °F): 	42 hPa (32 mm Hg)
· Density at 20 °C (68 °F):	1.06 g/cm³ (8.846 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
 Solubility in / Miscibility with 	····
· Water:	Not miscible or difficult to mix
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
dynamic:	Not determined.
· kinematic:	Not determined.



Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Cuttersil Hardener Universal Plus liquid

(Contd. of page 5)

Page 6/10

· Other information

No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

Possibility of hazardous reactions No dangerous reactions known

Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: none

· Additional information: -

11 Toxicological information

· Information on toxicological effects

Acute toxicity:

· LD/LC50 values that are relevant for classification:

78-10-4 tetraethyl orthosilicate

Oral LD50 6270 mg/kg (rat)

Dermal LD50 5878 mg/kg (can)

870-08-6 dioctyltin oxide

Oral LD50 >4000 mg/kg (rat)

681-84-5 tetramethyl orthosilicate

Oral LD50 700 mg/kg (rat)

· Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: Irritating effect.

· Sensitization: Sensitization possible through skin contact.

· Additional toxicological information: Harmful

· Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

Aquatic toxicity:

78-10-4 tetraethyl orthosilicate

EC50/48h >844 mg/l (daphnia)

(Contd. on page 7)

USA -



Page 7/10

Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Cuttersil Hardener Universal Plus liquid

(Contd. of page 6)

870-08-6 dioctyltin oxide EC50/48h 6.9 mg/l (daphnia)

LC50/96h 13 mg/l (fish)

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
 - General notes: Avoid transfer into the environment.
- · Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation

Small quantities can be polymerized with the matching system component(s) and the cured solid material can be disposed of with the regular garbage. Larger quantities must be disposed of following the regulations of the local authorities.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

UN1993
1993 FLAMMABLE LIQUID, N.O.S., special provision 640D (TETRAETHYL SILICATE)
FLAMMABLE LIQUID, N.O.S. (TETRAETHY) SILICATE)



Page 8/10

Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Cuttersil Hardener Universal Plus liquid (Contd. of page 7) · Label 3 · ADR · Class 3 (F1) Flammable liquids · Label · IMDG, IATA · Class 3 Flammable liquids · Label 3 Packing group • DOT, ADR, IMDG, IATA III· Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids · Danger code (Kemler): 30 · EMŠ Number: F-E,S-E · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · UN "Model Regulation": UN1993, FLAMMABLE LIQUID, N.O.S., 3, III 15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
 SARA Section 355 (extremely hazardous substances)

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act) Medical devices are exempted from TSCA.

· Cancerogenity categories

· TLV (Threshold Limit Value established by ACGIH)

870-08-6 dioctyltin oxide

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

A4



Page 9/10

Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Cuttersil Hardener Universal Plus liquid (Contd. of page 8) Hazard pictograms GHS06 GHS07 GHS02 GHS08 · Signal word Danger · Hazard-determining components of labeling: tetraethyl orthosilicate dioctyltin oxide tetramethyl orthosilicate · Hazard statements Flammable liquid and vapor. Toxic if inhaled. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. Do not breathe dust/fume/gas/mist/vapors/spray. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out. 16 Other information These data are based on our present knowledge. However, they shall not constitute a guarantee for any

specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapor.

- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Date of preparation / last revision 06/03/2017 / 2
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

- NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)
- LC50: Lethal concentration, 50 percent

(Contd. on page 10)

USA



Page 10/10

Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Cuttersil Hardener Universal Plus liquid

(Contd. of page 9)

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity – Category 4 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 • * Data compared to the previous version altered.

USA -