Version: 8.0

Effective Date: Mar-26-2020 Previous Date: Dec-17-2017



# SAFETY DATA SHEET LIQUICLEAN 103

#### 1. Identification

Product identifier LIQUICLEAN 103

Other means of identification None.

**Recommended use**Membrane cleaner **Recommended restrictions**None known.

### Company/undertaking identification

SUEZ WTS USA, Inc. 4636 Somerton Road Trevose, PA 19053

T 215 355 3300, F 215 953 5524

#### **Emergency telephone**

(800) 877 1940

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsSkin corrosion/irritationCategory 1B

Serious eye damage/eye irritation Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. Causes serious eye damage. May cause respiratory

irritation.

**Precautionary statement** 

**Prevention** Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a

well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response Immediately call a poison center/doctor. Wash contaminated clothing before reuse. If swallowed:

Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

**Storage** Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information

None.

# 3. Composition/information on ingredients

#### **Mixtures**

Components	CAS#	Percent
Hydroxyacetic acid	79-14-1	10 - 20
N-hydroxyethylenediamine triacetic acid trisodium salt	139-89-9	10 - 20
Sodium glycollate	2836-32-0	1 - 2.5

**Composition comments** 

Information for specific product ingredients as required by the U.S. OSHA HAZARD COMMUNICATION STANDARD is listed. Refer to additional sections of this SDS for our assessment of the potential hazards of this formulation.

#### 4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion

Do not induce vomiting. Rinse mouth. Call a physician or poison control center immediately. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

**General information** 

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Fire fighting equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In case of fire and/or explosion do not breathe fumes. Cool containers / tanks with water spray.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

## 6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Methods and materials for containment and cleaning up Wear appropriate protective equipment and clothing during clean-up. See Section 8 of the SDS for Personal Protective Equipment. Keep unnecessary personnel away. Do not breathe mist or vapor. Local authorities should be advised if significant spillages cannot be contained.

Ventilate the area. Soak up with inert absorbent material. Place in waste disposal container. Flush area with water. Wet area may be slippery. Spread sand/grit. Use water spray to reduce vapors or divert vapor cloud drift.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

Page: 2 / 9 Material name: LIQUICLEAN 103

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground. Water contaminated with this product may be sent to a sanitary sewer treatment facility, or a permitted waste treatment facility, in accordance with any local agreements.

# 7. Handling and storage

Precautions for safe handling

Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Acidic. Do not mix with alkaline material.

Conditions for safe storage, including any incompatibilities

Keep away from strong bases. Store locked up. Store in original tightly closed container. Keep container tightly closed in a dry and well-ventilated place. Do not freeze. If frozen, thaw completely and mix thoroughly prior to use. Store in accordance with local/regional/national/international regulation.

# 8. Exposure controls/personal protection

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

### Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

**Hand protection** 

Wear appropriate chemical resistant gloves. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Glove selection must take into account any solvents and other hazards present.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA'S 29 CFR 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

**Appearance** 

Colorless to amber Color

Physical state Liquid

Odor Slight acetic acid odor

Not available. **Odor threshold** 3.4 Neat pH (concentrated product)

pH in aqueous solution 3.3 (5% Solution) Melting point/freezing point -5 °F (-21 °C) Initial boiling point and boiling

range

210 °F (99 °C)

Not applicable. Flash point **Evaporation rate** Slower than Ether Not applicable. Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

Page: 3 / 9 Material name: LIQUICLEAN 103

Vapor pressure 18 mmHg Vapor pressure temp. 70 °F (21 °C)

Vapor density > 1
Relative density 1.35

Relative density temperature 70 °F (21 °C)

Solubility(ies)

Solubility (water) 100 %

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.Viscosity50 mPa.sViscosity temperature70 °F (21 °C)

Other information

Explosive properties

Oxidizing properties

Not explosive.

Not oxidizing.

Pour point

-0.04 °F (-18 °C)

Specific gravity 1.35

VOC 10 % ESTIMATED

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

**Conditions to avoid** Avoid contact with incompatible materials.

Hazardous decomposition Oxides of carbon and sulphur evolved in fire.

products

### 11. Toxicological information

## Information on likely routes of exposure

**Inhalation** May cause irritation to the respiratory system.

Skin contact Causes severe skin burns.

Eye contact Causes severe eye burns.

**Ingestion** Causes digestive tract burns. Ingestion may cause severe irritation of the mouth, the esophagus

and the gastrointestinal tract.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result. May cause respiratory irritation.

# Information on toxicological effects

# Acute toxicity

Product	Species	Species Test Results	
LIQUICLEAN 103 (CAS Mix	ture)		
Acute			
Dermal			
LD50	Rabbit	> 5000 mg/kg, (Calculated according to GHS additivity formula)	
Inhalation			
LC50	Rat	> 5 mg/l, 4 Hours, (Calculated according to GHS additivity formula)	
Oral			
LD50	Rat	4923 mg/kg, (Calculated according to GHS additivity formula)	

Material name: LIQUICLEAN 103 Page: 4 / 9

**Test Results** Components **Species** 

Hydroxyacetic acid (CAS 79-14-1)

Acute

Inhalation

LC50 Rat 3.6 mg/L, 4 Hour

Oral

LD50 Rat 2040 mg/kg

N-hydroxyethylenediamine triacetic acid trisodium salt (CAS 139-89-9)

Acute

Inhalation

LC50 Rat > 10.054 mg/l, 4 Hour

Oral

LD50 Rat 1780 mg/kg

Sodium glycollate (CAS 2836-32-0)

Acute

Oral

LD50 Rat

7110 mg/kg

Skin corrosion/irritation Causes skin burns.

Serious eye damage/eye

Causes serious eye damage.

irritation

Respiratory or skin sensitization

Respiratory sensitization This product is not expected to cause respiratory sensitization.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity Not classified. Carcinogenicity Not classified.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Based on available data, the classification criteria are not met. Aspiration of this product may

cause the same corrosiveness/irritation impacts as if it were ingested.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

#### **Ecotoxicity**

Product		Species	Test Results
LIQUICLEAN 103 (CA	AS Mixture)		
Aquatic			
Crustacea	LC50	Daphnia magna	1890 mg/L, Static Renewal Bioassay, 48 hour, (pH adjusted)
	NOEL	Daphnia magna	1060 mg/L, Static Renewal Bioassay, 48 hour, (pH adjusted)
Fish	0% Mortality	Fathead Minnow	2000 mg/L, Static Bioassay with 48-Hour Renewal, 96 hour, (pH adjusted)

#### Bioaccumulative potential

Material name: LIQUICLEAN 103 Page: 5 / 9

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Partition coefficient n-octanol / water (log Kow)

Hydroxyacetic acid -1.11 Sodium glycollate -5.19

**Bioconcentration factor (BCF)** 

Sodium glycollate 3

Mobility in soilNo data available.Other adverse effectsNot available.

Persistence and degradability

COD (mgO2/g) 335 (calculated data)
 BOD 5 (mgO2/g) 70 (calculated data)
 BOD 28 (mgO2/g) 105 (calculated data)
 Closed Bottle Test (% 23 (calculated data)

Degradation in 28 days)

- Zahn-Wellens Test (% 27 (calculated data)

Degradation in 28 days)

- TOC (mg C/g) 150 (calculated data)

# 13. Disposal considerations

**Disposal instructions**Dispose of contents/container in accordance with local/regional/national/international regulations.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code**The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Via an authorized waste disposal contractor to an approved waste disposal site, observing all local

and national regulations. Since emptied containers may retain product residue, follow label

warnings even after container is emptied. Empty containers should be taken to an approved waste

handling site for recycling or disposal.

## 14. Transport information

DOT

UN number UN3265

**UN proper shipping name** Corrosive liquid, acidic, organic, n.o.s. (Hydroxyacetic acid)

Transport hazard class(es)

Class 8
Subsidiary risk Packing group ||

Special precautions for user Not available.

ERG number 153

Some containers may be exempt from Dangerous Goods/Hazmat Transport Regulations, please check BOL for exact container classification.

IATA

UN number UN3265

**UN proper shipping name** Corrosive liquid, acidic, organic, n.o.s. (Hydroxyacetic acid)

Transport hazard class(es)

Class 8
Subsidiary risk Packing group II
Environmental hazards No.
ERG Code 153

Special precautions for user Not available.

**IMDG** 

UN number UN3265

UN proper shipping name CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Hydroxyacetic acid)

Transport hazard class(es)

Class 8 Subsidiary risk -

Material name: LIQUICLEAN 103 Page: 6 / 9

Packing group

**Environmental hazards** 

Marine pollutant No.

EmS F-A, S-B

Special precautions for user Not available.

Ш

DOT



IATA; IMDG



# 15. Regulatory information

**US federal regulations** 

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard Skin corrosion or irritation

categories Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Material name: LIQUICLEAN 103 Page: 7 / 9

Inventory status

Country(s) or region Inventory name On inventory (yes/no)\*

Canada Domestic Substances List (DSL) Yes

Canada Non-Domestic Substances List (NDSL) No

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## **US state regulations**

#### **California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

No ingredient listed.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

No ingredient listed.

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

No ingredient listed.

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

No ingredient listed.

## 16. Other information, including date of preparation or last revision

Issue dateJul-03-2014Revision dateMar-26-2020

Version # 8.0

NFPA ratings Health: 3

Flammability: 0 Instability: 0

NFPA ratings



List of abbreviations CAS: Chemical Abstract Service Registration Number

NFPA: National Fire Protection Association

ACGIH: American Conference of Governmental Industrial Hygienists

TWA: Time Weighted Average STEL: Short Term Exposure Limit LD50: Lethal Dose, 50% LC50: Lethal Concentration, 50% EC50: Effect Concentration, 50% NOEL: No Observed Effect Level COD: Chemical Oxygen Demand BOD: Biochemical Oxygen Demand

TOC: Total Organic Carbon

CEN: European Committee for Standardisation IATA: International Air Transport Association

IMDG: International Maritime Dangerous Goods Code

TSRN indicates a Trade Secret Registry Number is used in place of the CAS number.

OSHA: Occupational Safety & Health Administration.

**References:** Safety data sheets of raw materials.

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Material name: LIQUICLEAN 103 Page: 8 / 9

**Revision information** Hazard(s) identification: Prevention

Composition / Information on Ingredients: Disclosure Overrides Composition/information on ingredients: Composition comments

First-aid measures: Ingestion First-aid measures: Inhalation First-aid measures: Skin contact

Handling and storage: Conditions for safe storage, including any incompatibilities

Exposure controls/personal protection: Other Stability and reactivity: Conditions to avoid

Transport Information: Material Transportation Information

Regulatory information: California Proposition 65

Other information, including date of preparation or last revision: Bibliography

Other information, including date of preparation or last revision: List of abbreviations

**GHS: Classification** 

**Prepared by** This SDS has been prepared by SUEZ Regulatory Department (1-215-355-3300).

Material name: LIQUICLEAN 103