

Creation date: 08-26-19

Revision date: 06-21-21

Revision number: 1.2

## Section I - Product Identification

**Product:** A solution of USP grade water, USP grade isopropanol and a food grade blue dye. The product is also called rubbing alcohol.

**Intended Uses:** Intended to be used as rubbing alcohol and/or a topical disinfectant.

**Uses advised against:** Not for food use.

### Manufacturer Identification

Medical Chemical Corp.  
19430 Van Ness Ave.  
Torrance, CA 90501

Customer Service: Phone (310)787-6800  
Email: [Christinaavena@med-chem.com](mailto:Christinaavena@med-chem.com)  
FAX (310)787-4464



### Emergency Telephone Number

CHEMTREC Emergency Response Telephone Number: (800)424-9300. Note: The CHEMTREC phone number is only for emergencies involving spills, leaks, fire, exposure or accident. Please direct all other inquiries to our customer service phone number.

## Section II - Hazard Identification

This item is considered hazardous by 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

**Flammable liquid:** Category 2 (H225). Highly flammable liquid and vapor.

**Eye damage/eye irritation:** Category 2A (H319). Causes serious eye irritation.

**Acute toxicity (Oral):** Category 4 (H301). Toxic if swallowed.

**Acute toxicity (Inhalation):** Category 4 (H331). Toxic if inhaled.

**Signal word:** Danger

### Hazard statements

According to the harmonized classification and labeling required by OSHA and the EU, this substance is a highly flammable liquid and vapor, causes serious eye irritation and may cause drowsiness or dizziness. In case of skin contact remove all contaminated clothing. In case of fire, use fire extinguishers approved for alcohol fires.

### Precautionary statements

- P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautions against static discharge.
- P280 Wear protective clothes and eye protection.

### Safety Ratings

**Health:** Slightly hazardous **Flammability:** Highly flammable **Reactivity:** Stable **Contact:** Slight  
**Recommended safety equipment:** safety goggles, lab coat and proper gloves

### NFPA Ratings

Health = 1 Flammability = 4 Reactivity = 0

### Potential Health Effects

The toxicology of this compound has not been completely examined. It is presumed that the toxicity of this item is similar to other aliphatic alcohols. Vapors cause mild irritation of eyes and upper respiratory tract; high concentrations may be anesthetic. Liquid irritates eyes and may cause injury.

**Inhalation:** Alcohols are absorbed through the mucous membranes and will produce irritation as well as the same effects as ingestion.

**Ingestion:** Inhalation will produce CNS disturbance, dizziness, photophobia, headache, stupor, coma and death.

*Skin contact:* Usually harmless to skin. Repeated contact may cause irritation and flaking.

*Eye contact:* May be irritating.

*Chronic Exposure:* Unknown.

*Aggravation of preexisting conditions:* Impaired kidney and liver function may be aggravated by exposure to alcohols. Preexisting eye, skin, and respiratory conditions may also be aggravated.

### Section III - Composition/Information on Components

Ingredients	CAS #	EC/List #	%
Isopropanol	67-63-0	200-661-7	70% v/v

Also contains FD&C blue #1 as a dye.

### Section IV - First Aid Measures

*General Advice:* Contact a doctor if symptoms persist

*Inhalation:* Remove from source of exposure and get medical attention for any breathing difficulty.

*Ingestion:* Do not induce vomiting. Aspiration of alcohol into the lungs may produce death. Get immediate medical attention even if symptoms improve.

*Skin Contact:* In case of skin contact get medical advice if irritation develops.

*Eye Contact:* In case of eye contact, flush with water and get medical attention.

### Section V - Fire Fighting Measures

*Fire Extinguishing Media:* Alcohol foam, carbon dioxide or dry chemical. Water is ineffective against alcohol fires but may be used to cool adjacent containers.

*Flash point:* 22 °C (72 °F) TCC

*Flammable Limits (for isopropanol):* LEL 2% UEL 12%

*Specific Hazards:* Risk of vapor traveling to source of ignition and flashing back. Risk of exploding containers when heated. Vapor in air may form explosion risk.

*Special information:* Pyrolysis will release toxic carbon monoxide, formaldehyde and methanol.

*Special protective gear and precautions:* Self contained breathing apparatus and protective gear recommended.

### Section VI - Accidental Release Measures

Use personal protective gear, remove all sources of ignition, absorb with a suitable absorbent and dispose. Take precautions against static ignition. Should not be released into the environment.

### Section VII - Handling and Storage

P403+P233+P102; Store in a well-ventilated place. Keep container tightly closed. Store away from open flames or other sources of ignition. Keep out of reach of children.

### Section VIII - Exposure Control/Personal Protection

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropanol	400 ppm	400 ppm	2000 ppm

#### Legend

**ACGIH:** American Conference of Governmental Industrial Hygienists.

**OSHA:** Occupational Safety and Health Administration.

**NIOSH:** National Institute for Occupational Safety and Health.

**IDLH:** Immediately dangerous to life or health.

*Ventilation System:* Local exhaust such as explosion proof chemical fume hoods are recommended. When required, Refer to the ACGIH document, "Industrial Ventilation, a Manual of Recommended Practices" for details about ventilation.

*Personal Respirator:* Usually not required. In case of emergency, or when exposure levels are unknown, use a positive pressure, full face piece, air supplied respirator.

*Skin protection:* Usually not required.

*Eye Protection:* Laboratory safety goggles or similar products are not required but recommended as part of good laboratory practice.

---

## Section IX - Physical and Chemical Properties

*Boiling Point:* 180 °F (82 °C)

*Vapor pressure (mm Hg):* 33 @ 20 °C

*Vapor Density (air = 1):* 2.1

*Volatile organic carbon (VOC):* 549 g/l

Appearance and Odor: A clear colorless liquid with a sweet odor. Has the characteristic odor of isopropanol.

*Density:* 0.845 g/ml @ 20 °C

*Evaporation Rate (N-butyl alcohol = 1):* 1

*Solubility:* Infinitely miscible with water

Appearance and Odor: A clear colorless liquid with a

---

## Section X - Stability and Reactivity

*Stability:* Stable under normal conditions.

*Hazardous Decomposition Products:* Nothing unusual.

*Hazardous polymerization:* Will not occur.

*Incompatibilities:* Oxidizers, peroxides etc.

*Conditions to avoid:* heat, flame and sources of ignition.

---

## Section XI - Toxicological Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropanol	>4700 mg/kg (Rat)	13,000 mg/kg (Rabbit)	19,000 ppm/8h (Rat)

### Cancer lists

*Ingredient*                      *Known Carcinogenicity?*    *NTP?*    *Anticipated?*    *IARC Category*

Isopropanol                      no                                      no                      no                                      3

---

## Section XII - Ecological Information

Aliphatic alcohols evaporate quickly and are not expected to bioaccumulate. The material is removed from the air by dry and liquid adsorption.

**Environmental Fate:** Biodegradable

**Soil Mobility:** Unknown

**Environmental Toxicity:** Low.

Component	Freshwater Fish	Water Flea	Freshwater algae
Isopropanol	LC50 > 9640 mg/l 96 h	EC50 >7550 mg/l 48 h	EC50 >1000 mg/l 72 h

---

## Section XIII - Disposal Considerations

Disposal at a licensed chemical disposal facility is the preferred disposal method. Local governments often restrict the amounts of isopropanol and other flammable liquids that may be flushed down the drain. The usual rule is that the effluent exiting the building must not be flammable. Dispose of contents and container in accord with all applicable regulations.

---

## Section XIV - Transportation Information

*DOT Shipping name:* Isopropanol

*Hazard Class:* 3                      *Packaging Group:* II

*DOT Hazard Label:* Flammable liquid                      *DOT Identification Number:* UN1219

Bottles smaller than 32 Fl. Oz. are eligible to be shipped under limited quantity exemptions [49 CFR section 173.150(b)(2), 173.150(C) and IATA Y341].

---

## Section XV - Regulatory Information

### Chemical Inventory Status

*Ingredient*                      *TSCA*    *EC*

Isopropanol                      Yes                      Yes

**Federal and State Regulations**

<i>Ingredient</i>	<i>SARA 302</i>		<i>SARA 313</i>		<i>RCRA</i>	<i>TSCA</i>	<i>Ca. Prop 65</i>
	<i>RQ</i>	<i>TPQ</i>	<i>List</i>	<i>Category</i>	<i>261.33</i>	<i>8(D)</i>	
Isopropanol	No	No	Yes	No	No	No	No

Chemical Weapons Convention: No      TSCA 12(b): No      CDTA: Yes

SARA 311/312: Acute: Yes Chronic: No Fire: Yes Pressure: No Reactivity: No

---

**Section XVI - Other Information**

This information is believed to be correct at the time of publication but is not guaranteed as such, nor does it purport to be all inclusive. Medical Chemical Corp. assumes no liability for the accuracy or completeness of the information. The user assumes all responsibility for compliance with federal, state and local laws.

Document Number: S107

Revision number: 1.2

Revision Date: Jun. 21, 2021