

SAFETY DATA SHEET

Creation Date 03-Feb-2012	Revision Date 26-Jan-2015	Revision Number 1	
	1. Identification		
Product Name	100% Dehydrant		
Cat No. :	22-050-106, 6215, 6255		
Synonyms	Denatured Ethyl alcohol		
Recommended Use	Laboratory chemicals.		
Uses advised against No Information available Details of the supplier of the safety data sheet			
Company Richard Allan Scientific A Subsidiary of Thermo Fisher Scient 4481 Campus Drive Kalamazoo, MI 49008 Tel: (800) 522-7270	Emergency Telephone Number Chemtrec US: (800) 424-9300 Chemtrec EU: 001 (202) 483-7616		
	2. Hazard(s) identification		
Classification This chemical is considered hazardou	s by the 2012 OSHA Hazard Communication Standard	(29 CFR 1910.1200)	

Flammable liquids Specific target organ toxicity (single exposure) Target Organs - Central nervous system (CNS), Optic nerve.	Category 2 Category 1
Specific target organ toxicity - (repeated exposure) Target Organs - Kidney, Liver, spleen, Blood.	Category 1
Aspiration Toxicity	Category 1

Label Elements

Signal Word Danger

Hazard Statements

Highly flammable liquid and vapor May cause drowsiness or dizziness Causes damage to organs Causes damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways



Precautionary Statements Prevention Do not breathe dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Take precautionary measures against static discharge Wear protective gloves/protective clothing/eye protection/face protection Keep cool Response IF exposed: Call a POISON CENTER or doctor/physician Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell Skin IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower Fire In case of fire: Use CO2, dry chemical, or foam for extinction Storage Store locked up Store in a well-ventilated place. Keep container tightly closed Disposal Dispose of contents/container to an approved waste disposal plant Hazards not otherwise classified (HNOC)

None identified

Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous. WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

3. Composition / information on ingredients

Component	CAS-No	Weight %
Isopropyl alcohol	67-63-0	5.5
Ethyl alcohol	64-17-5	90
Methyl alcohol	67-56-1	4.5

4. First-aid measures			
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.		
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.		
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a respiratory medical device. Immediate medical attention is required.		
Ingestion	Do not induce vomiting. Call a physician or Poison Control Center immediately.		
Most important symptoms/effects	Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting		

Notes to Physician

Treat symptomatically

	5. Fire-fighting measures
Suitable Extinguishing Media	CO 2, dry chemical, dry sand, alcohol-resistant foam.
Unsuitable Extinguishing Media	Water may be ineffective
Flash Point Method -	13.9 °C / 57 °F No information available
Autoignition Temperature Explosion Limits	362.8 °C / 685 °F
Upper	19 vol %
Lower	3.3 vol %
Sensitivity to Mechanical Impac	
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO2) Formaldehyde

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA_ Health Flammability 2 3		Instability 0	Physical hazards N/A			
	6. Accidental re	lease measures				
Personal Precautions		quipment. Ensure adequate ver ry measures against static disc	ntilation. Remove all sources of harges. Do not get in eyes, on			
Environmental Precautions	Should not be released int information.	o the environment. See Section	n 12 for additional ecological			
Methods for Containment and C Up	Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.					
	7. Handling	and storage				
Handling	flames, hot surfaces and s	ources of ignition. Take precau -proof equipment. Do not breat	entilation. Keep away from open itionary measures against static he vapors or spray mist. Do not			
Storage	Keep containers tightly clo and sources of ignition. Fla		tilated place. Keep away from heat			
8.	Exposure controls	/ personal protecti	on			
Exposure Guidelines						

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 980 mg/m ³ (Vacated) STEL: 500 ppm (Vacated) STEL: 1225 mg/m ³ TWA: 400 ppm TWA: 980 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm (Vacated) TWA: 1900 mg/m ³ TWA: 1000 ppm TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m³
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m ³ (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m ³ Skin TWA: 200 ppm TWA: 260 mg/m ³	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Isopropyl alcohol	TWA: 400 ppm TWA: 985 mg/m ³ STEL: 500 ppm STEL: 1230 mg/m ³	TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³	TWA: 200 ppm STEL: 400 ppm
Ethyl alcohol	TWA: 1000 ppm TWA: 1880 mg/m ³	TWA: 1000 ppm TWA: 1900 mg/m³	STEL: 1000 ppm
Methyl alcohol	TWA: 200 ppm TWA: 262 mg/m ³ STEL: 250 ppm STEL: 328 mg/m ³ Skin	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 310 mg/m ³	TWA: 200 ppm STEL: 250 ppm Skin

Legend

ACGIH - American Conference of Governmental Industrial Hygienists NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures	Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.
Personal Protective Equipment	
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

	9. Physical and chemical properties
Physical State	Liquid
Appearance	Clear
Odor	aromatic
Odor Threshold	No information available
рН	No information available
Melting Point/Range	-114.1 °C / -173.4 °F
Boiling Point/Range	78.5 °C / 173.3 °F

Flash Point Evaporation Rate Flammability (solid,gas) Flammability or explosive limits Upper Lower Vapor Pressure Vapor Density Relative Density Solubility Partition coefficient; n-octanol/water Autoignition Temperature Decomposition Temperature Viscosity 13.9 °C / 57 °F No information available No information available 19 vol % 3.3 vol % 44 mmHg 1 24

1.24 0.8 Soluble in water No data available 362.8 °C / 685 °F No information available No information available

10. Stability and reactivity

Reactive Hazard None known, based on information available	
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Heat, flames and sparks.
Incompatible Materials	Strong oxidizing agents, Peroxides, Metals, Acids, Acid anhydrides, Acid chlorides
Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Formaldehyde	
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Oral LD50 Dermal LD50 Vapor LC50 Component Informa		No acute toxicity information is available for this product Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.				
Component		LD50 Oral		D50 Dermal	LC50	nhalation
Isopropyl alcol	hol	5840 mg/kg (Rat)				L(Rat)4 h
Ethyl alcoho	1	7060 mg/kg (Rat))	Not listed	20000 pp	m/10H(Rat)
Methyl alcohol		6200 mg/kg (Rat)	1580			m(Rat)4 h ′L(Rat)4 h
Toxicologically Syne Products Delayed and immedi	•	No information ava		d long-term expo	osure	
Irritation		Irritating to eyes				
Sensitization		No information available				
Carcinogenicity		The table below indicates whether each agency has listed any ingredient as a carcinogen.				
Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Isopropyl alcohol	67-63-0	Not listed				
Ethyl alcohol	64-17-5	Group 1	Not listed	A3	Х	Not listed
Methyl alcohol	67-56-1	Not listed				
LADO (lateration	IADO (Internetional Annual for Descents on Conserv)					

IARC: (International Agency for Research on Cancer)

IARC: (International Agency for Research on Cancer)

Mutagenic Effects	Group 1 - Carcinogenic to Humans Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans Mutagenic effects have occurred in humans.
Reproductive Effects	Adverse reproductive effects have occurred in humans.
Developmental Effects	Substances known to cause developmental toxicity in humans.
Teratogenicity	Teratogenic effects have occurred in humans.
STOT - single exposure STOT - repeated exposure	Central nervous system (CNS) Optic nerve Kidney Liver spleen Blood
Aspiration hazard	No information available
Symptoms / effects,both acute and delayed Endocrine Disruptor Information	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting No information available
Other Adverse Effects	Tumorigenic effects have been reported in experimental animals. See actual entry in RTECS for complete information.

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Isopropyl alcohol	1000 mg/L EC50 > 96 h 1000 mg/L EC50 > 72 h	1400000 μg/L LC50 96 h 11130 mg/L LC50 96 h 9640 mg/L LC50 96 h	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h
Ethyl alcohol	EC50 (72h) = 275 mg/l (Chlorella vulgaris)	LC50 = 14200 mg/l/96h	Photobacterium phosphoreum:EC50 = 34634 mg/L/30 min Photobacterium phosphoreum:EC50 = 35470 mg/L/5 min	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h
Methyl alcohol	Not listed	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	EC50 > 10000 mg/L 24h

Persistence and Degradability Bioaccumulation/ Accumulation No information available No information available.

Mobility

Component	log Pow
Isopropyl alcohol	0.05
Ethyl alcohol	-0.32
Methyl alcohol	-0.74

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	-

14. Transport information

DOT	
UN-No	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	II
TDG	
UN-No	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	II
IATA	
UN-No	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	II
IMDG/IMO	
UN-No	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	
	15 Regulatory

15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Isopropyl alcohol	Х	Х	-	200-661-7	-		Х	Х	Х	Х	Х
Ethyl alcohol	Х	Х	-	200-578-6	-		Х	Х	Х	Х	Х
Methyl alcohol	Х	Х	-	200-659-6	-		Х	Х	Х	Х	Х

Legend: X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b)

Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Isopropyl alcohol	67-63-0	5.5	1.0
Methyl alcohol	67-56-1	4.5	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

Not applicable

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	Х		-

OSHA Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component		Hazardous Substances RQs	CERCLA EHS RQs		
Methyl alcohol		5000 lb	-		
California Proposition 65	This product	contains the following Proposition 65 ch	nemicals: Ethyl alcohol is only a		

considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage

Component	CAS-No	California F	California Prop. 65		o 65 NSRL	Category		
Ethyl alcohol	64-17-5	Developm	Developmental		nental -		-	Developmental Carcinogen
Methyl alcohol	67-56-1	Developm	pmental -		-	Developmental		
State Right-to-Know								
Component	Massachusetts	New Jersey	Pennsy	ylvania	Illinois	Rhode Island		
Isopropyl alcohol	Х	Х	>	K	-	Х		
Ethyl alcohol	Х	Х	>	K	Х	X		
Methyl alcohol	Х	X	>	κ	X	X		

U.S. Department of Transportation

Reportable Quantity (RQ):	Y
DOT Marine Pollutant	Ν
DOT Severe Marine Pollutant	Ν

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class

B2 Flammable liquid D1B Toxic materials D2A Very toxic materials



Prepared By

Regulatory Affairs

Richard Allan Scientific A Subsidiary of Thermo Fisher Scientific Tel: (800) 522-7270

Creation Date Revision Date Print Date Revision Summary 03-Feb-2012 26-Jan-2015 26-Jan-2015 This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS